









Protection





Protection

Product Features

- 1. ABS CASE, ANTI-SPLASH
- 2. 1/2" BSP INLET/OUTLET
- 3. 55° C Over temperature protection &85 $^{\circ}$ C dry heating protection

Technology

- 4. RED COPPER HEAT EXCHANGER
- 5. KNOB REGULATION THERMOSTAT

Control Protection

- 6. THREE POWER SETTING MODE
- 7. POWER OPTION: 3.0kW/3.5kW/5.5kW/8.0kW

Technical Date-Overall Dimensions

Model		KIS-80C
Capacity	L	ENDLESS
Power	KW	3.0/3.5/5.5/8.0
Voltage	V	220-240
Heating Efficiency	%.	≥96
Max working Temperatur	$^{\circ}$	55
Min Water Pressure	Мра	0.2
Product Size	L*W*H/cm	30*18.5*9.5
Temp Cutting	$^{\circ}$	93

WARNING:technical dimensions could be varied by the manufactures without notice and the above information is indicative only.

Released by Dingxin Electric Appliance Co.,LTd.,

No 71, Xinyi Road, Sanjiang Industrial Zone, Shengzhou, Zhejiang China. Website: www.dincn.com Ph:+86-057583793313,Fax: +86-057583793318