



Full Automatic Temperature

- 1. ABS CASE, ANTI-SPLASH
- 2. 1/2" BSP INLET/OUTLET
- 3. 55 °C OVER TEMPERATURE PROTECTION & 85 °C DRY HEATING PROTECTION
- 4. ALUMNIUM CAST HEAT EXCHANGER
- 5. LED DISPLAY AND TOUCH SCREN CONTROL

Technology

- 6. FLOW BASED OPERATION
- 7. POWER OPTION: 3.5kW/5.5kW

Technical Date-Overall Dimensions

Model		GIU-60S
Capacity	L	ENDLESS
Power	KW	3.5/5.5
Voltage	V	220-240
Heating Efficiency	%.	≥96
Max working Temperatur	°C	55
Min Water Pressure	Мра	0.2
Product Size	L*W*H/cm	26.0*26.0*6.5
Temp Cutting	°C	93

WARNING:technical dimensions could be varied by the manufactures without notice and the above information is indicative only.

Released by Dingxin Electric Appliance Co., LTd., No 71, Xinyi Road, Sanjiang Industrial Zone, Shengzhou, Zhejiang China. Website: www.dincn.com Ph:+86-057583793313,Fax: +86-057583793318

Safety Forecast Anti-splash Protection

Electric Leakage Protection

Electric Leakage Protection Warning